

11/22/00

A

ORIGINAL/CIP PATENT APPLICATION TRANSMITTAL LETTER

ATTORNEY'S DOCKET NO.
RD-27,500/USA

TO THE ASSISTANT COMMISSIONER FOR PATENTS:

Transmitted herewith for filing is the ☒ ORIGINAL ☐ CONTINUATION-IN-PART patent application of:

Wu Wang James Pelligrino Alexander

Christopher Anthony Kaminski

Robert John Nygard

Inventor(s)

For REMOVABLE SELF-LOCKING FIELD WINDING BLOCK

(Title of Invention)

☐ This is a Continuation-In-Part of Serial No. _____, filed _____, Attorney Docket No. _____

ENCLOSED ARE:

- ☒ Specification having 10 total pages.
- ☒ 2 sheets of ☐ formal ☒ informal drawings.
- ☒ Declaration. ☐ Unsigned Declaration.
- ☐ Information Disclosure Statement.
- ☐ Other _____
- ☒ An Assignment of the invention to General Electric Company with cover sheet.

The filing fee is calculated below:

	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE \$710.00
TOTAL CLAIMS	14 - 20 =	0	x \$18.00	\$0.00
INDEPENDENT CLAIMS	2 - 3 =	0	x \$80.00	\$0.00
ADDITIONAL FEE FOR USE OF MULTIPLE DEPENDENT CLAIM(S) (once per application)			x \$270.00	
TOTAL FILING FEE				\$710.00

- ☒ Please charge \$710.00 to my Deposit Account No. 07-0868.
- ☒ The Assistant Commissioner is hereby authorized to charge payment of all fees required under 37 CFR 1.16 or 1.17 or credit any overpayment to Deposit Account No. 07-0868.

Oct. 25, 2000
date

Marvin Snyder
Attorney Marvin Snyder
Reg. No 20,126

Send Correspondence to:
General Electric Company
CRD Patent Docket Rm 4A59
P.O. Box 8, Bldg. K-1 -Salamone
Schenectady, New York 12301

"Express Mail" mailing label number _____

Date of Deposit _____

Customer Number: 006147

Three copies of this form are enclosed

REMOVABLE SELF-LOCKING FIELD WINDING BLOCK

This application claims the benefit of U.S. Provisional Patent Application Serial No. 60/169,241, filed December 6, 1999, the entire content of which is herein incorporated by reference.

5 BACKGROUND OF THE INVENTION

This invention relates to multi-pole electric machines and, more particularly, to a self-locking block for a field winding in a rotor assembly.

10 In a conventional electric machine such as a generator having a rotor and a stator, the rotor is provided with field windings that excite the machine while receiving current from an excitation source. The stator is provided with armature windings from which electrical power is provided.

15 Conventional rotors include axially oriented slots to restrain the winding against centrifugal forces. At the end regions, retaining rings or the like are used to contain the end windings. Due to different radial stiffness of the rotor and retaining ring, bending stresses are generated, and material fatigue becomes a concern. A loose winding may also cause motion of mass, resulting in balance drifts. The issue becomes more significant when lower stiffness composite materials are used for the retaining rings.

20 It is thus desirable to develop a robust field winding blocking system to control winding position and to reduce its movement on the rotor. Winding blocks can provide adequate pre-stress to keep the winding tight over the design range of spin speeds and provide a well-defined reference position, preventing peripheral dissymmetry in the rotor.

BRIEF SUMMARY OF THE INVENTION

In an exemplary embodiment of the invention, a rotor assembly includes a rotor forging having a rotor body with pole faces, a winding module including a plurality of field windings positioned adjacent the pole faces and winding insulators disposed between each of the field windings, respectively, and a winding block disposed in engagement with the winding module. The winding block is shaped to be shifted to a final position relative to the winding module when the rotor assembly rotates at about its rated speed to thereby compress the winding module.

In another exemplary embodiment of the invention, a multi-pole electric machine rotor assembly includes a rotor forging having a rotor body with poles extending along the direct axis and fins extending along a quadrature axis. Each pole includes a pole face extending generally perpendicularly to the direct axis. A winding module includes a plurality of field windings positioned in spaces between the pole faces and the fins. Winding insulators are disposed between each of the field windings. A winding block is disposed between the winding module and a corresponding one of the fins in each of the spaces between the pole faces and the fins. Preferably, a winding block is movably detached from the fins and the winding module. The winding block may include a support surface engaging a corresponding one of the fins and a tapered surface engaging the winding module. At least one angle of the tapered surface is preferably selected such that the winding block is shifted to a final position when the rotor assembly rotates at about its rated speed. A friction coefficient of the tapered surface may also be selected such that the winding block is shifted to its final position when the rotor assembly rotates at about its rated speed. The winding block is preferably formed of a flexible insulating material.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a cross sectional view of the rotor assembly of the invention;

Figure 2 is a perspective view of the rotor forging without the winding
5 assemblies installed thereon; and

Figure 3 illustrates an alternative arrangement for effecting blocking of the rotor windings shown in Figure 1.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 is a partial cross section of a rotor assembly 10 including a
10 two-pole rotor forging 12 with poles 13 directed along the d axis (direct axis) and having pole faces 14 extending substantially perpendicularly to the d axis. Winding assemblies 16 are slid over parallel sides of poles 13, and the entire rotor assembly is contained within a tubular rotor housing 18. Figure 2 is a
15 perspective view of the rotor assembly before the winding assemblies are slid over the parallel sides of poles 13. This three-dimensional representation illustrates the poles extending along the d axis and fins 22 extending along the q axis (quadrature axis). As shown in Figure 1, a shield 20 or the like may also be interposed between housing 18 and both rotor forging 12 and winding assembly 16 as shown.

20 In order to increase a section bending moment of inertia along the q-axis, fins 22 may be arranged to extend along the q-axis as part of rotor forging 12. The fins provide a well-defined position reference for winding modules 16, as well as a well-defined locking interface for spacer blocks 24 between winding modules 16.

25 As shown, in Figure 1, winding modules 16 include a plurality of field windings 25 positioned in spaces between pole faces 14 and fins 22. A

winding insulator 26 is interposed between each successive pair of field windings, respectively. A spacer block (or winding block) 24 is preferably disposed between each winding module 16 and a corresponding one of fins 22, respectively, in each space between a pole 13 and a corresponding one of fins 22.

Winding blocks 24 include a support surface 24a engaging a corresponding one of fins 22 and a tapered surface 24b engaging winding modules 16. The winding blocks are preferably formed of a flexible insulating material, such as a glass fiber reinforced composite, having a friction coefficient that effects a locked position of the winding blocks.

As the rotor spin speed increases during operation, winding blocks 24 are shifted radially outward by centrifugal force, locking in their final positions at or slightly above rated speed. The winding blocks are particularly configured to achieve this result; that is, the parameters of winding blocks 24, including the angle of the tapered surface, the friction coefficient, the length of the blocks, etc., determine the manner and extent to which winding blocks 24 react during operation. Preferably, the winding blocks are engineered to have minimum resistance for radially outward motion, and a friction angle that substantially prevents radially inward motion. Using statistical analysis, the amount of slack in the windings during operation, resulting from assembly clearances, tolerance take-up during rotation, etc., is determined. Based on length of the block, the block friction angle that will significantly reduce or eliminate slack in the windings at or about rated speed, is determined within a standard deviation.

When the rotor returns to zero speed, winding blocks 24 are locked in their final positions by friction and maintain the compression and tightness in winding modules 16; that is, although winding blocks 24 can be readily removed, in their final positions, the angle of the tapered surface and the block coefficient of friction serve to lock the winding blocks in their final

positions, thereby maintaining the compression in winding modules 16. In this context, the stiffness of winding modules 16 is selected using various materials to develop sufficiently small residual stresses in the winding, thereby avoiding damage to the winding and its insulation. An objective is a "tight" winding after the initial spin, without over-stressing the winding components.

The rotor assembly of the invention may alternatively be constructed of a rotor forging 12 that does not include fins 22. In this context, a block 24 is placed between each respective pair of successive field windings 26.

Moreover, the blocks or corresponding structure may be fixed in the assembly with an oppositely wedged construction, whereby the field windings are compressed by radial displacement across the blocks during rotation. An example of this construction is illustrated in FIGURE 3, wherein winding blocks 24 are fixedly positioned adjacent windings 26. In operation, as the rotor assembly is rotated at about its rated speed, winding modules 16 are displaced radially outwardly over winding blocks 24, thereby compressing the windings. Similar to the embodiment of Figure 1, the angle of the tapered surface and coefficient of friction of winding blocks 24 serve to lock the assembly in a final compressed position. Thus a final position of winding blocks 24 relative to windings 26 can be effected by displacement of the winding blocks, for example as shown in FIGURE 1, or by displacement of the windings, for example as shown in FIGURE 3.

As described above, a robust field winding blocking system thus serves to control the winding position and reduce its alternating radial movements. The winding blocks provide adequate pre-stress to keep the winding tight over the design range of spin speeds and provide a well-defined reference position preventing peripheral dissymmetry in the rotor.

While only certain preferred features of the invention have been illustrated and described, many modifications and changes will occur to those

skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention

WHAT IS CLAIMED IS:

1. A rotor assembly comprising:

a rotor forging including a rotor body having pole faces;

5 a winding module including a plurality of field windings positioned adjacent the pole faces and a winding insulator disposed, respectively, between each pair of successive field windings, respectively; and

10 a winding block disposed in engagement with the winding module and shaped to be shifted to a final position relative to the winding module when the rotor assembly rotates at about its rated speed to thereby compress the winding module.

2. A rotor assembly according to claim 1, wherein the winding block comprises a tapered surface engaging the winding module.

15 3. A rotor assembly according to claim 2, wherein the tapered surface friction coefficient is selected such that the winding block is shifted to the final position relative to the winding module when the rotor assembly rotates at about its rated speed.

4. A rotor assembly according to claim 1, wherein the winding block is formed of a flexible insulating material.

20 5. A rotor assembly according to claim 1, wherein the winding block is fixed in its position on the rotor assembly, and wherein the winding module is displaced across the winding block when the rotor assembly rotates at about its rated speed.

6. A multi-pole electric machine rotor assembly comprising:

25 a rotor forging including a rotor body having poles directed along a direct axis with pole faces extending generally perpendicularly to a direct axis, and fins extending along a quadrature axis;

a winding module including a plurality of field windings positioned in spaces between the pole faces and the fins, and a winding insulator disposed between each successive pair of the field windings, respectively; and

5 a winding block disposed between the winding module and a corresponding one of the fins in each respective one of the spaces between the pole faces and the fins.

7. A rotor assembly according to claim 6, wherein the winding block is movably detached from the fins and the winding module.

10 8. A rotor assembly according to claim 7, wherein the winding block comprises a support surface engaging the corresponding one of the fins and a tapered surface engaging the winding module.

9. A rotor assembly according to claim 8, wherein the tapered surface angle is selected such that the winding block is shifted to a final position when the rotor assembly rotates at about its rated speed.

15 10. A rotor assembly according to claim 9, wherein the tapered surface friction coefficient is selected such that the winding block is shifted to a final position when the rotor assembly rotates at about its rated speed.

20 11. A rotor assembly according to claim 6, wherein the winding block comprises a support surface engaging the corresponding one of the fins and a tapered surface engaging the winding module.

12. A rotor assembly according to claim 11, wherein the tapered surface angle is selected such that the winding block is shifted to a final position when the rotor assembly rotates at about its rated speed.


25 13. A rotor assembly according to claim 12, wherein the tapered surface friction coefficient is selected such that the winding block is shifted to a final position when the rotor assembly rotates at about its rated speed.

14. A rotor assembly according to claim 6, wherein the winding block is formed of a flexible insulating material.

REMOVABLE SELF-LOCKING BLOCK OF FIELD WINDING

ABSTRACT OF THE DISCLOSURE

A multi-pole electric machine rotor assembly includes a rotor forging including a rotor body having poles 13 with pole faces and a winding module including a plurality of field windings positioned adjacent the pole faces and winding insulators disposed between each successive pair of the field windings, respectively. A winding block, disposed in engagement with the winding module, is shaped to be shifted to a final position relative to the winding module when the rotor assembly rotates at about its rated speed to thereby compress the winding module. Either the winding block or the winding module can be displaced by centrifugal forces during rotation. In the final position, the winding block is locked by friction in a position to maintain compression in the winding module. The winding block serves to provide a pre-stress in the field windings to keep the field windings tight over the design range of spin speeds, thereby controlling winding position and reducing alternating radial movement.






FIG. 3

DECLARATION FOR PATENT APPLICATION

Docket Number
RD-27,500/USA

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:
REMOVABLE SELF-LOCKING FIELD WINDING BLOCK

the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____ as United States Application Number or PCT International Application Number _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56. I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application

Priority Claimed

☐ Yes ☐ No

(Number) (Country) (Day/Month/Year Filed)

☐ Yes ☐ No

(Number) (Country) (Day/Month/Year Filed)

I hereby claim the benefit under Title 35, United States Code, §119(e) of any **United States provisional application(s)** listed below.

60/169,241 12/6/99
(Application Number) (Filing Date)

(Application Number) (Filing Date)

I hereby claim the benefit under Title 35, United States Code §120 of any **United States Application(s)** listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Number) (Filing Date) (Status - patented, pending, abandoned)

(Application Number) (Filing Date) (Status - patented, pending, abandoned)

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith


Douglas E. Stoner, Reg. No. 26,509, Marvin Snyder, Reg. No. 20,126, Donald S. Ingraham, Reg. No. 33,714, Jill M. Breedlove, Reg. No. 32,684, Noreen C. Johnson, Reg. No. 38,929, Ronald E. Myrick, Reg. No. 26,315, Henry J. Policinski, Reg. No. 26,621 and Jay L. Chaskin, Reg. No. 24,030.

Address all telephone calls to: Marvin Snyder at telephone number (518) 387-6189


Address all correspondence to: **General Electric Company**
CRD Patent Docket Rm 4A59
P.O. Box 8, Bldg. K-1 - Salamone
Schenectady, New York 12301

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


SOLE OR FIRST INVENTOR:

Full name: Yu Wang
First Name Middle Name Last Name
 Signature:  Date 8/29/2000
 Residence: Clifton Park, New York Citizenship: USA
City and State
 Post Office Address: 28 Spruce Street, Clifton Park, New York 12065


SECOND JOINT INVENTOR:

Full name: Christopher Anthony Kaminski
First Name Middle Name Last Name
 Signature:  Date 11 Sept 00
 Residence: Niskayuna, New York 12309 Citizenship: USA
City and State
 Post Office Address: 11 Shelburne Court, Niskayuna, New York 12309

THIRD JOINT INVENTOR:

Full name: Robert John Nygard
First Name Middle Name Last Name
 Signature:  Date 9/10/2000
Saratoga Springs 9/10/2000 RPN
 Residence: Saratoga Spa, New York Citizenship: USA
City and State
 Post Office Address: 57 Lougherry Road

FOURTH JOINT INVENTOR:

Full name: James Pelligrino Alexander
First Name Middle Name Last Name
 Signature:  Date 9/20/2000
 Residence: Ballston Lake, New York Citizenship: USA
City and State
 Post Office Address: 12 Northwest Pass, Ballston Lake, New York 12019